# EASY-FLOW NO DROP AIR CLEANER

## **CALENCOD** PROCESS MACHINERY AIR CLEANERS

# THE UNMATCHED QUALITY OF AN EASY-FLOW & ONE LESS DROP

## **CALAKEWOOD** Easy Flow No Drop

- All stainless steel construction
- Easy-to-access debris collection cage
- Telescopic adjustable height legs
- Adjustable infeed height independent from main frame & exit end

Produce is fed onto the inclined conveyor either directly or into the optional metering hopper. Product is conveyed through the air stream all on one stainless steel wire belt conveyor to ensure fewer drop points and gentle handling through the debris removal process. Small and lighter berries, leaves, and debris follow the air stream into the overhead cage where it is conveyed out to one side via two 'trash' conveyors. The first conveyor carries out berries while the second conveyor carries out lighter sticks and leaves.

### **Easy Flow No Drop Capacities**

| Working Width | Capacity (lbs per hour)           |
|---------------|-----------------------------------|
| 33″           | Approximately 8,000 lbs per hour  |
| 42″           | Approximately 12,000 lbs per hour |

#### **Easy Flow No Drop Options**

| Conveyor Options          |
|---------------------------|
| Stainless Steel Wire Belt |
| Fine Mesh SS Wire Belt    |
|                           |

| Infeed Length Options |  |
|-----------------------|--|
| 6′                    |  |
| 9′                    |  |
| 12′                   |  |

Additional

options include:

(a) Extended Discharge Conveyor Length

(b) Lug Rack beneath Trash Discharge for Trash Collection

(c) Controls & Trash Discharge (LH or RH)

(d) Metering Hopper (shown at right)

