

# FLAT INSPECTION CONVEYORS



INSPECTION CONVEYORS

## A SIMPLE FLAT SORTING CONVEYOR FOR YOUR FRESH LINE

Product is fed onto the conveyor belt where grading personnel stand along each side and visually inspect the product for defects. Defect product is manually removed and dropped into the trash lanes along the edge of each side of the conveyor. Good product continues along the length of the conveyor and discharges off of the end of the belt while defects are dropped through a trash chute at the exit end of the conveyor and into a lug below.

### Flat Inspection Conveyor Capacities

Working Width	Capacity (lbs per hour)
24"	Approximately 6,000 lbs per hour
30"	Approximately 7,000 lbs per hour
33"	Approximately 8,000 lbs per hour
36"	Approximately 9,000 lbs per hour
42"	Approximately 12,000 lbs per hour

### (Standard) Flat Inspection Conveyor Options

Width	Belt Type	Lengths Available per Width / Belt
24"	Rubber	10' / 14'
30"	Rubber	14' / 18'
30"	SS Wire	12'
33"	SS Wire	15'
36"	Rubber	12' / 18'
36"	SS Wire	15'
42"	SS Wire	20'

### Flat Inspection Conveyor Add-on Options

#### Light Kits

Overhead light kits available for most conveyor lengths



### LAKWOOD PROCESS MACHINERY Flat Rubber Belt Inspection

- All stainless steel construction
- Easy, wipe-clean design
- Nonstaining, smooth rubber belting
- Trash collection lug rack for 30lb (or smaller) lugs
- 3" Flip-up, hinged trash lanes

### LAKWOOD PROCESS MACHINERY Flat Wire Belt Inspection

- All stainless steel construction
- Easy-to-clean Sprocket Driven SS Wire Belt
- Easy-to-clean Plastic Intralox Belt 3" Trash Lanes
- Trash collection lug rack for 30lb (or smaller) lugs